

Technical Specifications		
MODEL		SE-HT-19U
Heating Capacity	KW	18.4
COP		4
Power Supply		380~415V/50Hz/3Ph
Input Power	KW	4.6
Rated Current	A	11.8
Rated Water Temperature	°C	75
Max Water Temperature	°C	80
Heat Exchanger (Condenser)		Brazed Plate Heat Exchanger / Tube in Shell
Evaporator		Blue Finned Evaporator Coil
Throttling Valve		Thermostatic Expansion Valve/Electronic Expansion Valve
Refrigerant		R134a
Compressor		Scroll (Copeland/Panasonic/Sunniva)
Number of compressor		1
Fan Quantity	Piece	1
Rated Hot water output @ 60°C	LPH	530
Rated Hot water output @ 70°C	LPH	370
Rated Hot water output @ 80°C	LPH	280
Water Flow	m³/hr	3.3
Water Pressure Drop	KPa	≤50
Weight	kg	205
Noise at 1 Meter	dB(A)	≤62
Pipe Size	inch	R1
Dimension	mm	800 X 800 X 1025
Test Condition: Ambient Temp. (DB/WB)=20deg C./15 deg C., Inlet Water Temp. = 55 deg C., Outlet Water Temp. = 60 deg C. (E.T. 10 deg C./ C.T. 65 deg.)		

